

Skudo TNT 250

Resin-coated polyester non-woven fabric

Presentation

Skudo TNT 250 is a 250 g/m² special resin-coated polyester non-woven fabric, about 1 mm thick. It comes in 50 m x 1 m rolls.

Applications

Skudo TNT 250 is mainly used to reinforce waterproofing coatings made using our bituminous elastomeric water-based liquid membrane, **ElastiK**, when this is applied on concrete slabs or flat roofs on which tiles will be laid or a concrete screed will be made.

Skudo TNT 250 is also used as a porous support on which to attach tiles using the **ElastiK System** (a solution to refurbish balconies and terraces without removing the old floor, or to waterproof new balconies without having to create the usual 5 cm concrete screed on which tiles are laid).

Operating instructions

Do not apply **ElastiK** on the surface first, then, after a few minutes, apply the **Skudo TNT 250** support: **ElastiK** would dry up immediately and the **Skudo TNT 250** would not stick. Instead:

- 1) Place the **Skudo TNT 250** roll on the surface to treat.
- 2) Apply a strip of **ElastiK** in front of the roll, using a large brush. Then, on the fresh product, immediately apply the **Skudo TNT 250** reinforcing support, pressing it with your feet or a brush to help **ElastiK** penetrate into the fabric.

Warnings

Skudo TNT 250 can be preserved for a long time if kept in its original package and out of direct sunlight.

Rev. 01/01/2014

EDILCHIMICA S.r.l.

Via Bergamo, 23 – 20098 S. Giuliano Milanese (MILANO) ITALY Tel. +39 02 98280912/13 Fax +39 02 98281051

e-mail: info@edilchimica.com www.edilchimica.com